

Malvern Hills Area of Outstanding Natural Beauty

Consultation Draft

Guidance on the selection and use of colour in development



Contents

General guidance

Introduction 2

How to use this guide 4

Principles of exterior colour design **5**

Introduction to NCS 8

The colour palettes

High Hills and Slopes and Unenclosed Commons 9

Principal Wooded Hills, Principal Timbered Farmlands and

Wooded Hills and Farmlands 17

Forest Smallholdings and Dwellings (Wellington Heath) 28

Settled Farmlands with Pastoral Land Use 33

Settled Farmlands on River Terraces and Sandstone Estatelands 38


Enclosed Commons 46

Welland **52**

Appendices

Appendix 1: Materials xx

Appendix 2: NCS – RAL Translation Key (not included in draft) **xx**



Introduction

1.1 Colour and the landscape

The landscape of the Malvern Hills and surrounding areas has been designated as an Area of Outstanding Natural Beauty (AONB) with the primary purpose of conserving and enhancing its natural beauty. Both natural and cultural influences have combined to produce the landscape that is so highly valued today.

Colour makes an important contribution to the special character and local distinctiveness of the area. As well as the seasonal colours of spring and autumn, the bedrock colours of granites, sandstone and limestone give rise to different soil colours and different patterns of vegetation. Management and landuse also influence the colours we see, varying between improved pasture, unenclosed grasslands, intensively cropped orchards and arable land. Winter tones show the landscape at its most essential, illuminated by low winter sunlight. Local building materials of brick, stone, timber, render, slate and tile, create another layer of colour which adds to the distinctiveness of the area.

As the population of the area grows, and as pressure for change increases, it is vital that careful consideration is given to the use of colour when selecting materials and finishes for new development. Getting this right will help to ensure not only that development fits with the special landscape of the AONB, but that it in turn will contribute to the local distinctiveness of the area.

1.2 The purpose of this document

This purpose of this document is to provide direction and guidance on the selection and use of colour associated with development within the Malvern Hills AONB. 'Development' includes any building work, ranging from home extensions and conversions through to house building, fencing, agricultural and industrial premises, retail and office buildings. In this context, development also includes infrastructure and finishes associated with transport and utilities.

This document should be read in association with the other documents published by the AONB Partnership, in particular the Guidance on Building Design which contains essential information on appropriate development within the AONB.

1.3 Who this document is for

This document provides guidance for everyone considering or proposing development within the AONB, including landowners, property owners, developers, agents, advisers, architects and landscape architects. It is also targeted at those with responsibility for setting the framework for development and for making decisions about individual planning applications. This includes planning staff and their colleagues in local authorities.

The guidance in this document will help those who value and care for this area to ensure that future developments contribute to the sense of place.

1.4 Status of this Guidance

This document has been produced to help implement the Malvern Hills AONB Management Plan which 'formulates local authority policy for the management of the AONB and for the carrying out of their functions in relation to it' (Section 89 of the Countryside and Rights of Way Act 2000). The AONB Management Plan is a material consideration in relation to planning. The Guidance amplifies the content of the Management Plan in relation to development in the AONB.

Using this document will help public bodies to meet their statutory duties to have regard to the purposes of conserving and enhancing the natural beauty of the AONB in exercising of performing any functions in relation to, or so as to affect AONB land (Section 85 of the Countryside and Rights of Way Act 2000).

1.5 A word on methodology

The guidance contained in this document is based on the principle that colour is never seen in isolation from its setting. Selecting colours for building materials has to take account of the site context if good choices are to be made. Indigenous site colours throughout different parts of the AONB have been documented, analysed, and synthesised into 'existing palettes' which represent the essential colours that belong to those areas. Working with these palettes it has been possible to create 'developed palettes' of colour appropriate to a range of building materials, which will help to integrate new development into the landscape.

This process of analysis and design is known as Environmental Colour Assessment. It presents a logical approach to a subject which many people regard as a matter of taste, and therefore beyond objectivity. However, this process creates a robust insight into the colours of specific places, creating developed palettes from which people can still exercise preferences for particular colours, but in the knowledge that these colours will work with the site.

The Environmental Colour Assessment was undertaken in the winter months of 2015/16, and therefore clearly reflects the seasonal colours prevalent at that time. However, winter is an advantageous time of year to make the study as the landscape is at its most elemental and exposed. Foliage, and the play of light and shade on leaf canopies, can distract the eye and even screen new interventions in the landscape. No such diversions exist in winter, so it is a valuable time to judge colours. In addition, it should be recognised that whilst the incidence, proportions and visibility of colour will vary through with seasons there is a consistency of colours present throughout the year. Therefore, colours selected from a winter palette will always be relevant.

How to use this guide

2.1 Step 1: Read the 'Principles of exterior colour design' notes

Working through the questions will make you aware of what to look out for and help you to decide what you want to achieve with the colour design.

2.2 Step 2: Familiarise yourself with the Natural Colour System (NCS)

It is not essential to be an expert in its application but a basic knowledge will help you to understand colour terminology and how to communicate your ideas., see page 9 and www.ncscolour.co.uk

2.3 Step 3: Locate your development site on the Landscape Character Map (page 2)

NB: A more detailed map will be available in the final guidance.

2.4 Step 4: Examine the 'Existing Palette' and associated site survey photographs for the Landscape Character Type or settlement within which your development site sits

This will help you to understand the provenance of the selected colours. If possible walk the area, take in views to your site from outside of the area and pay close attention to the colours you see. You may decide at this stage to review your decision at Step 3 and also include additional Landscape Character Types because of their visual connection to your site.


2.5 Step 5: Examine the 'Developed Palette(s)' for the Landscape Character Type(s) or settlement, which relates to your development site

- **a)** Identify the materials you are most likely to be using with reference to the titles on the left hand side of the palette.
- **b)** Select a colour for the principal elevations, (side and /or walls) of your development from the 'Integration Colour' column, which relates to that material.
- **c)** Work across to the right in line with the colour you have selected. You will have the option to select a neutral grey and a tinted grey, which will work with your initial choice, useful as a 'bridge' between older parts of a building and newer additions.
- **d)** Continue to work across to the right on the same line and select an accent colour which may be used elsewhere on your development such as window and door frames, or to highlight a particular aspect of your design.

The list of materials and their respective colours is not exclusive, but includes suggestions for colours generally available in different types of material. In the case of applied colours such as masonry paint, it is acceptable to choose from any of the colours illustrated on the palette.

2.6 Step 6: Refer to Appendix A for product information for a range of materials which may be suitable for use in your development

The colour ranges of these products will be similar to the colours illustrated in the palette. In the event that you cannot get the exact colour selected from the palette, then look for the closest match. The list of products is representative only, and as with the colour guidance is there to provide general advice and not strict specification.



Principles of exterior colour design

Colour guidance for development within the AONB is aimed at integrating new buildings into the landscape in a way that benefits both the landscape and the built form. This can range from effectively camouflaging or minimizing the visual appearance of a utilitarian building to emphasizing the specific qualities of a place through the architecture, expressed in colour, form and massing. Good colour choices depend upon a good understanding of the proposed development in relation to its landscape setting.

The following checklist gives an idea of the issues involved.

3.1 Is the development 'background architecture' or 'signature architecture'?

Small scale domestic development, village expansion, and developments associated with farming and rural industries will often be designed to fit within the grain, colour and texture of the local environment. Signature buildings may have a presence and scale which allows a more dynamic use of colour and materials, interacting with, and complementing the landscape setting, but also standing out against it. The guidance contained in this documents deals primarily with the former type of development. If your scheme is of the latter type then you may wish to extend the relevant developed palette into more complementary or accented colours, or a different range of materials.

3.2 Where are the key views to the development?

It is necessary to anticipate the key viewpoints from which the completed development will be seen. Some viewpoints may be more sensitive than others and require an approach with colour which minimises the impact of the building, whilst others may require a stronger approach to aid the legibility of the scheme.

3.3 From what distance will the development be seen?

Whilst the nature of hue alters with distance, tonal contrasts between built form and landscape remain largely constant. Therefore if a development will be visible from afar, and the intention is to 'lose' it in the landscape then the tonal qualities of the colour rather than the hue of the colour become particularly important. In this case it will be preferable to select tones which match or are slightly darker than the landscape when seen from a view point. If the intention is to create a landmark in the distance, then select much lighter tones than are present in the landscape.

3.4 Is light reflectivity an issue?

Sunlight striking a surface can substantially alter the perceived colour making it both lighter and brighter in the landscape. South-facing elevations and inclined roofs will be particularly prone to this effect.



Highly reflective roofing material

can be highly reflective. It is possible to find some matt finishes to paint work in different colours, or to find alternative materials such as fibre cement. If there is no realistic alternative to steel then select a dark tone for roofing material as these reflect less light than a light coloured sheet. Slates are another material where sheen can be problematic. Natural slate will weather back to a matt finish with some colour variations, however, manmade equivalents tend to remain consistent in colour and sheen for longer.

As a general rule matt integration colours will sit better in a rural context allowing for patterns of light and shade to animate surfaces. Matt finishes are particularly important when considering development which sits in important views, especially from above. North facing elevations will remain in the shade and potentially will remain wetter for longer. If the material is affected by rain, such as lime wash or timber, its perceived colour will be darker and the hue may also shift when wet.

3.5 What is the key landscape context within the visual frame of the development?

The colour palettes in this guidance have been set out according to the Landscape Character Type (LCT) categorisations which exist for the area. However, due to the often undulating topography of the AONB, only considering the LCT within which the development site sits may not provide the full information needed to appraise the visual context. This is particularly significant for developments on the margins of LCTs, where rising ground or woodland plantations, located within a different character type actually provide a more significant backdrop. Thoroughly analysing the site before referring to the palettes will help to ensure colour selection from the appropriate group.

3.6 Does the building form require articulation to aid legibility or to influence scale?

Introducing a different colour or material can help 'guide' people around a building, making its use more intuitive. If the scale of a building looks too large for its setting, introducing another colour of a dark recessive nature will help to diminish the apparent scale of the building, by breaking up its massing.

A general rule of thumb is to only introduce a change of colour/material, where it makes sense to do so, eg. for recessed or projecting panels, or where there are legibility or structural reasons. In general the more three dimensional elevations appear, the more interesting they are, on the other hand too many colours can make a building appear fussy and confused.

3.7 Does the development address textures occurring within its landscape?

Colour and material choices also need to be informed by the background texture of the landscape setting. This requires analysing adjacent building materials, and vernacular detailing,



and also the dominant vegetation and ground finishes to understand the depth of relief, play of light and shade and range of tactile surfaces. These observations will help determine appropriate finishes and textures for the development.

3.8 Are the materials used colour-fast? How will they weather?

High chromaticness in dark colours especially reds often results in fading under UV light. Natural materials like timber will also fade and this needs to be anticipated before specification. Whilst there is often a reluctance to stain newly constructed timber cladding it should be recognised that the same cladding will look quite different after a few summers.

3.9 What is the effect of distance on colour?

Research shows that the perceived colour of a building façade, seen from some distance, tends to look less dark and more chromatic or brighter than the inherent colours of the material from which it is constructed. In other words a colour sample which may look slightly dull in the studio as a swatch will look more colourful and lighter on the façade. The developed colour palettes in this guidance have been largely adjusted from the existing palettes to take account of this with a low level of chromaticness, and an increase in blackness. This quality of 'blackness' is of great importance as this represents the tone or nuance of a colour. The effect of tone on the visibility of a building against a distant landscape has been referred to above. The difference in tone between a building and its surroundings is probably the most important factor contributing to recognition of its form.

Hues can also change with distance. Perceived colours are often lighter and brighter than samples, with the exception of greens and yellows which tend towards blue when seen from a distance. In a study carried out in Sweden on this phenomenon, green close up became darker blue green at 2km and lilac grey at 20km.

All natural green inherent colours have some yellowness in them though this does vary with seasonality and land management. If a developer wishes to use green on a development, and for it to appear green at a distance, then a green with a higher degree of yellow will be needed. Assumptions are frequently made that the only suitable colour for developments in rural areas, especially large scale industrial and agricultural developments is green. However many of the greens available as standard colours in suppliers' ranges do not contain enough yellow and black and the result is a glaring mis-match with the surroundings. This reinforces the point that tonality or nuance is all important, especially when it is difficult to get the right hue.

3.10 Is simultaneous contrast an issue?

Simultaneous contrast occurs when the same colours look different when viewed against different backgrounds. In attempting to distinguish the colour against the background, the human eye tends to reinforce and exaggerate that difference. In reality this is more difficult to observe against a polychromatic background of shifting vegetation than it is against the controlled and hard surfaces of a building façade, and is more of an issue for the detailed articulation of a building. In addition, the seasonal variations which occur within a landscape mean that dramatic changes in background colour are relatively short lived and the perception of this phenomenon is more often altered by changing light conditions. Whilst it is useful to be aware of simultaneous contrast other factors are likely to be more influential within the realm of integrating development into the AONB.

Whatever colour choices are made, it is prudent to create a large sample to take it to site before committing to full scale application. Examining a small sample under artificial light indoors can offer misleading information.

Overleaf are some images which illustrate good and bad practice in colour application and selection.




Good colour mix for tiles, timber and brick. In keeping with the Unenclosed Commons Landscape Character Type



Partly right, partly wrong: light coloured doors and too many materials




Soft, harmonising colours containing a lot of grey with weathered timber and silver birch working well together





Colours much too light with no attempt to relate to wooded background

Introduction to NCS

In order to accurately communicate the colours we see, we need a reference or notation system with the ability to pinpoint precise colour.








Six Elementary Colours are the basis for the Natural Colour System. These are White, Black, Yellow, Red, Blue and Green. The colours are shown below on the three dimensional model called the NCS Colour Solid. Every colour in the Natural Colour System is contained within the NCS Colour Solid, and can be described in terms of the six Elementary Colours.

In order to more easily pinpoint colours within the NCS Colour Solid, the NCS Colour Circle and NCS Colour Triangle are used.

The NCS Colour Circle is a horizontal slice through the NCS Colour Solid, and shows a progression from Yellow to Red to Blue to Green and back round to Yellow in 10% steps.

All the colours in the NCS System have a percentage of Whiteness or Blackness, and this is best illustrated using the NCS Colour Triangle. The NCS Colour Triangle is a vertical slice through the NCS Colour Solid. C stands for maximum colour intensity or Chromaticness, W stands for White and S for Black. The scales for Chromaticness, Whiteness and Blackness are each divided into one hundred parts which can be interpreted as percentages.

The NCS Colour Triangle and the NCS Colour Circle are used to pinpoint colours within the NCS System. The diagram (top right) pinpoints a colour with 30% Blackness and 20% Chromaticness, with a location on the NCS Colour Circle of G30Y. The complete NCS Colour Notation is S 3020-G30Y.



Using the NCS Colour Notation it is easy to define the appearance of a colour. In this notation (right) 3020 indicates the Nuance of the colour. The Nuance describes the relationship of the colour to Black (S) and to maximum colour intensity or Chromaticness (C). The Whiteness is determined as 50%, as the sum of the values of the three attributes (Chromaticness, Whiteness and Blackness) must always be 100%. The Hue, G30Y, describes the relationship of the colour to the Chromatic Elementary Colours, in this case G and Y. G30Y means Green with 30% Yellow. The letter S preceding the NCS notation means that the colour is from NCS Edition 2.

Achromatic colours (Black, White and Grey) lack Hue and are only given Nuance notations, followed by -N for neutral. S 0500-N is White and is followed by S 1000-N, S 1500-N, S 2000-N and so on to S 9000-N, which is Black.

NCS Colour Notation

NCS S 3020-G30Y

High Hills and Slopes and Unenclosed Commons




The developed palette on page 16 is built around the unimproved and unenclosed nature of acid heath and grassland present in both Landscape Character Types.

Lighter colours reflect the tussock forming grasses and scrub, rough grazing over thin soils, and grey reds of bracken and birch. Darker integration colours and their accent counterparts reflect the distant views to hilltops and the passing patterns of cloud over the landscape, lending blues, greys and lilacs to the range. Traditional brick colours, timber frame colours and hard Malvern stone colours are also represented in the palette.






























































































Principal Wooded Hills, Principal Timbered Farmlands, Wooded Hills and Farmlands



The developed palette on page 27 reflects the common characteristics of these three Landscape Character Types. Woodland blocks, hedgerow trees and dense hedges, interspersed with tracts of farmland, some of it unimproved, outlined in places with intimate water courses, and narrow lanes.

The palette is built around the winter tones and hues of native trees, seen in block and silhouette, sometimes against a backdrop of evergreens but more typically against pasture. The colours derived from this are soft grey greens, green yellows and grey browns, with lighter colours derived from winter branches and harvested fields. The building materials of traditional buildings such as timber, brick and render can also be seen in this palette.











































































































































Principal Timbered Farmlands and Wooded Hills and Farmlands Principal Wooded Hills, Developed Palette:

Forest Smallholdings and Dwellings (Wellington Heath)



The developed palette on page 32 reflects the intimate relationship between the village and its immediate surroundings. Set within a steep valley, views are generally internal and short ranged, framed and closed with hedges, small pasture lands and trees. Where longer views exist they are often spectacular, sometimes encompassing the textures and patterns of intensive commercial orchards or key features such as the contours of the British Camp.

The palette contains the colours of vegetation and tree bark, especially the ubiquitous birch, seen in close quarters throughout the settlement. It also contains the earthy ochre of local stone and the soft oranges of traditional brick. Many of the colours in the palette are suitable for timber cladding or timber framing, a construction detail common to several dwellings in the village. The lighter colours in soft tones respond to the play of light and shade, whilst the darker tones provide a sense of enclosure and solidity.














































Settled Farmlands with Pastoral Land Use




The developed palette on page 37 is derived from the largely pastoral nature of this Landscape Character Type. The greens vary from orchards and unimproved rough grazing through to fields bounded by mature hedgerows with occasional trees. Some darkened versions of these hues are found in the integration colours but many more, in softer tones, contribute to the range of accent colours. Balance to the palette is provided by the rich colours and tones of traditional orange red bricks and timber framed buildings.
















































Settled Farmlands on River Terraces and Sandstone Estatelands



The developed palette on page 45 reflects the dominant land use of these Landscape Character Types. Fertile sandy soils are readily seen beneath commercial orchards and in arable cropping lands. The winter hues of fruit trees combined with the red brown soil colours underpin the colour range. Underlying red sandstone enriches the palette with deep and dense colours, reinforced by dark timber framed buildings, masonry and traditional brick.



























































































Enclosed Commons



This developed palette on page 51 follows the pastoral land use which is characteristic across much of the Unenclosed Commons Landscape Character Type, with a range of grey yellow/greens reflecting the varied nature of the sward. Darker tones pick up the well defined hedgerows, and arable land where this occurs.

The palette incorporates a range of off-whites and creams, derived from the landscape but significantly lightened, for render and paint application and also a range of masonry and brick colours reflecting the traditional dwellings in the area. Accent colours provide opportunities to animate and articulate wayside dwelling extensions and new builds with colours drawn from all sectors of the colour wheel. The darkest colours are reserved for agricultural buildings and other associated uses.


















MALVERN HILLS AONB GUIDANCE ON THE SELECTION AND USE OF COLOUR IN DEVELOPMENT CONSULTATION DRAFT






























Welland




The village of Welland is developing rapidly with new housing underway in early 2016 and more planned. The developed palette on page 56 recognises this with a focus on the colours of construction, but derived from the more traditional buildings to minimise the risks of ubiquitous urbanisation.

Brick, stone, tile and slate colours are provided with reference also made to the landscape context of unenclosed commons, small orchards and the high hills and slopes of the Malvern Hills. New housing, especially that designated for sites to the west of the Gloucester Road, would benefit from drawing upon the landscape colours present in the palette to maintain a sense of local identity.







































Appendix A

This appendix contains a list of just some of the available building materials which may be suitable for use on developments within the AONB area. This is by no means an exclusive list and the Malvern Hills AONB Partnership is not endorsing or recommending the products or manufacturers listed. Alternative materials and suppliers are available.

Metal Cladding and Roofing

1. Tata Steel www.colorcoat-online.com produces a range of profiled steel sheet, from which the following colours may be considered:

Colorcoat HPS200 Ultra:

Anthracite (Ral 7016) nearest NCS 7502-B.

Merlin Grey (Ral 180 40 05) nearest NCS 6005-B20G.

Ardenne (Ral7022) nearest NCS 7005-Y20R.

Mole Brown (Ral 070 40 10) nearest NCS 7010-Y10R.

Moorland Green (Ral 100 60 20) nearest NCS 4010-G70Y.

Svelte Grey (Ral 080 50 20) nearest NCS 4005-Y20R.

Olive Green (Ral 100 30 20) nearest NCS 7010-G50Y.

Terracotta (Ral 040 40 40) nearest NCS 5030-Y70R.

Juniper Green (Ral 140 20 20) nearest NCS 8010-G50Y.

Van Dyke Brown (Ral 8014) nearest NCS 7502-Y.

Green Grey (Ral 150 40 10) nearest NCS 8005-Y20R.

Anthracite, Green Grey, Oxidised and Terracotta are also available as matt sheets. Matt sheets should always be considered for roofing. Light reflection on pitched steel roofs can distort the colour substantially, rendering even dark colours as very light, a matt finish helps to reduce this risk.

Colorcoat LG is a similar range of colours as above but with a leathergrain finish and not specifically matt.

Colorcoat Prisma:

Slate Grey (Ral 7012) nearest NCS 6502-B.

Anthracite (Ral 7016) nearest NCS 7502-B.
Terracotta (Ral 040 40 40) nearest NCS 5030-Y70R.

Anthracite and Terracotta are also available as matt sheets and as such these should always be considered for roofing.

- **2. Euroclad** www.euroclad.com produce a range of metal profiled sheet. The Vieo range of wall and roof cladding uses material from the Colorcoat HPS 200 Ultra range and Colorcoat Prisma range. Standing seam cladding is also available from Tata Steel in the Colorcoat Urban range, with a similar choice of matt colours.
- **3. Thomas Panels and Profiles** www.panelsandprofiles.co.uk produces a range of roofing and cladding sheets, sharing some of the colours with Colorcoat HPS200 Ultra:

Vandyke Brown, Merlin Grey, Olive Green, Terracotta, Juniper green.

In addition:

Svelte Grey (BS 10B 23) nearest NCS 5010-G90Y Slate Blue (BS18B29) nearest NCS 7502-B

4. VMZ www.vmzinc.co.uk produces a range of cladding and roofing panels in zinc.

Natural VMZINC is shiny at first but develops a dull patina over time.

QUARTZ-ZINC is a self healing product, nearest NCS 4502-B.

ANTHRA-ZINC matches some slate colours and works well with PV panels. Nearest NCS 8505-Y20R.

PIGMENTO has the texture of QUARTZ-ZINC but is coloured:

Pigmento Blue, nearest NCS 6010-B10G, Pigmento Red, nearest NCS 6010-Y90R, Pigmento Green, nearest NCS 4005-G80Y, Pigmento Brown, nearest NCS 6005-Y80R.

Fibre Cement Cladding and roofing

1. Marley Eternit www.marleyeternit.co.uk produce a range of fibre cement products for cladding:

Cedral Lap has a standard range of 23 colours and comes in plank sizes of 3600 mm. x 190mm. Colours worth considering include:

Sage green NCS 4010-G90Y Forest Grey NCS 8005-G80Y Pearl NCS 4005-G80Y Pewter NCS 5500-N Cream White NCS 0502-Y Beige NCS 0505-Y20R

Cedral Lap can be matched to any NCS co-ordinate providing the order exceeds the minimum quantity for specials.

Cedral Click tongue and groove planks are available in a standard range of 7 colours. Colours worth considering include:

Grey NCS 3502-R, Grey Brown NCS 3005-Y20R, Cream White, Beige.

Marley Eternit also produce through coloured fibre cement boards in the Equitone Range.

The following colours from the Natura range of Equitone are worth considering:

Natural Grey NCS 5005-G80Y Fossil Grey NCS 4005-G80Y Autumn Dusk NCS 4005-Y20R Sepia NCS 7005-Y20R

Equitone Pictura Range, (not through coloured)

Mocha NCS 5005-Y50R Fawn Grey NCS 3502-R Equitone Linea Range:

Hessian NCS 4005-Y50R

Equitone Tectiva range (through coloured with grain)

Sahara NCS 3030-Y70R Hessian NCS 4005-Y50R Linen NCS 2005-Y20R Calico NCS 1002-Y50R.

Marley Eternit also produce profiled fibre cement for roofing. Within their range the following colours may be useful:

Tawny Brown NCS 3040-Y60R Bracken NCS 5010-Y50R Van Dyke Brown NCS 7502-Y Anthracite NCS 6502-Y Blue NCS 7502-B Laurel NCS 8010-G50Y

Render

- **1. K Rend** www.K-Rend.co.uk produce silicone thin coat render in a wide range of NCS colours. An NCS fan deck is available from their Technical Support Centre.
- **2. Wetherby Building Systems** www.wbs-ltd.co.uk produce thin coat renders to cover external insulation refurbishments. The HECK range offers a wide range of NCS colours, including:

1010-Y20R

1010Y

1015Y

0520-G90Y

0520-Y10R

0520-Y20R

3030-Y50R

5010-B90G

2030-Y10R

4005-R50B

5502-Y

5502-B

7500-N

3. Ty Mawr www.lime.org.uk offers a range of premixed natural hydraulic limes, such as St. Astier EcoMortar C, F and WP to a standard range but will also mix to any NCS colour.

Ty Mawr also provides Glaster, a mix of lime binder with recycled glass aggregate suitable for external and internal applications with colour provided by the glass and natural pigments added to the lime.

Masonry Paint

- **1. Dulux Trade** www.duluxtrade.co.uk offer Weathershield for exterior wood, metal and masonry. The colour palette bears similarities with NCS and Dulux tinting machines recognize NCS coordinates. Dulux also produce a range of Heritage finishes derived from research into period colours.
- **2. Armstead Trade** www.armsteadtrade.co.uk part of the Akzo Nobel group as are Dulux offer a fan deck with the full range of 1950 NCS colours.
- **3. Crown Trade** www.crowntrade.co.uk offer Sandtex for exterior wood, metal and masonry with a similar colour range to Dulux and with tint machines which also recognize NCS codes. Crown also produce a range of historic colours.
- **4. Keim Mineral Paints** www.keimpaints.co.uk have a wide range of breatheable mineral and silicate paints to suit a variety of substrates and conditions. Equivalent NCS references can be given for their range upon request.
- **5. Ty Mawr** www.lime.org.uk have a wide range of mineral based paint for interior and exterior situations. All Ty Mawr paint products are classified using NCS coordinates.

Wood finishes

- **1. Dulux Trade** www.duluxtrade.co.uk offer a range of 600 colours in their opaque wood stain collection. They also offer a designer range and a natural wood colour range though only some of these are suitable for exterior application. As with the trade palette NCS coordinates can be recognized by tinting machines.
- **2. Sikkens** www.sikkens.co.uk are also part of the AkzoNobel group and offer a variety of professional woodcare systems. Rubbol exterior opaque coating system offers colours from NCS, Ral, BS4800 and their own 4041 colour concept range. The Cetol Systems for Exterior offers two collections, Classic and Style with finishes in transluscent and opaque, matches to NCS will need to be made by visual comparison.
- **3. Beeck** www.beeck.com produce plant based wood paint in semi –gloss finish to NCS classification. It is available in the UK through Ty Mawr
- **4. Crown** www.sadolin.co.uk produce Sadolin wood stains in opaque and translucent finishes using their own colour range for Superdec and Beach Hut colours, they also offer colours in Ral Classic and BS4800.

Translation tables exist between Ral and NCS.

Building Boards

- **1.Rock Panel** www.rockpanel.co.uk produce compressed pre formed building boards for cladding in a range of 24 standard colours. For orders in excess of 100m any NCS colour may be specified. NCS equivalents for the standard range may be given upon request.
- **2. Trespa** www.trespa.com produce building boards in a standard range of 67 colours. Special colours can be produced for significant projects.

Colours worth considering include:

Mid Grey NCS 5000-N Taupe NCS 6010-Y90R Cactus Green NCS 4010-G70Y Natural Greige NCS 6005-Y50R

Bricks

There are very many bricks available on the market, this selection has been made to get reasonable matches to the range of traditional bricks found within the AONB area.

1. Furness Brick www.furnessbrick.co.uk

Natural orange NCS 3040-Y50R Grey brown NCS 6010-Y50R Burlington Orange NCS

2. Terca www.weinerberger.co.uk

Autumn Russet Sovereign Stock NCS 3030-Y60R Witton Multi Stock NCS 3050-Y50R Warnham terracotta stock NCS 3050-Y50R

3. **Ibstock** www.ibstock.com

Mercia Orange NCS 5030-Y50R Himley Worcestershire Mix NCS 5030-Y50R Berkshire Orange Stock NCS 4040-Y50R

It should be noted that due to variation in brick colours, especially multis, the colour reference is approximate only and other factors such as texture and finish should be considered when choosing bricks. A sample panel of a metre square is advisable when selecting bricks.

Mortar

The colour of pointing mortar can have a profound effect on the appearance of brickwork, and to a lesser extent on blockwork.

The sample panel of brickwork referred to above is also the opportunity to test mortar colours.

1. Tarmac www.tarmac.com/mortar/mortar produce over 50 shades of factory produced mortar.

For the brick colours mentioned above, use a mid tone to dark grey from 5005-7005 on the NCS grey tint scale

Tarmac Y79 is a dark lilac NCS 7005-R20B and works well with bricks NCS 3040-Y50R. Y80 and Y76 are also worth considering.

- **2. Premier Mortars** www.premiermortars.co.uk have a similar range of 48 shades of mortar, PM66, PM92,and PM94 are worth sampling alongside your brick panels.
- **3. Ty Mawr** www.lime.org.uk supply natural hydraulic lime mortars for natural breathability and elasticity:

Lithomex Stone Resoration and Repair Mortar comes in 4 standard colours and can also be colour matched to a particular stone.

Hourdex is a grey mortar.

RJ35 Pre-mixed lime mortar is available in many shades of beige.

Clay tiles and slates

Clay tiles come in many profiles, the plain tile with a cross cambered surface is traditional to the area.

1. Sandtoft www.sandtoft.com produce natural clay plain tiles:

Village Plain Reclaimed NCS 7020-Y80R, NCS 8010-Y90R, NCS 6020-Y80R.

Alban Plain Tile, Sussex Blend NCS as above but greater proportion of darker tones.

Handcrafted plain Tile in Lichen Green is also worth consideration.

Concrete tiles are generally not acceptable in the area.

Slates are also common place in the area, traditionally from Wales. Welsh slate can still be purchased, though generally at a premium price.

2. Welsh Slate Ltd www.welshslate.com produce roofing colours as follows:

Cwt-y-bugail a dark blue grey slate NCS Penrhyn a heather blue slate NCS

Cheaper real slate is imported from Spain. NB The colour varies with the quarry from which it comes.

3. Stoneleaf www.stoneleafslates.co.uk supplies a slate close to the hue of welsh slate, called Celtic Grey.

Reclaimed Welsh slate can be found from architectural reclamation yards.

4. Monier Redland www.monier.co.uk produce manufactured slate which once weathered is a viable substitute to real slate:

Cambian Heather NCS
Cambrian grey weathered NCS

Aggregates for landscaping

It is important that the strong local colour range is reflected in the use of sands, gravels and aggregates within developments.

1. Radbournes www.radbournes.co.uk supply a range of decorative aggregates some of which come from relatively local sources:

Hereford gravel comes in 6mm-20mm sizes and ranges from pink to grey, the smaller aggregate has an overall colour of NCS 6010-Y70R to NCS 5020-Y60R.

Malvern stone sits at Y50R to Y80R with a nuance of 5030 to 6020 so this is a reasonable match.

Other aggregates from Radbournes include:

Weeford 14mm from Shropshire

Forest of Dean clean 10mm-20mm from Gloucestershire.

Though not directly from this area the colour sits within a range of local stone.

The following bodies provide financial support to the Malvern Hills AONB Partnership



Supported by













Malvern Hills AONB Partnership Manor House, Grange Road Malvern, Worcestershire WR14 3EY

Tel: 01684 560616 Fax: 01684 577457

Email: aonb@worcestershire.gov.uk Web: www.malvernhillsaonb.org.uk